

Package `mactivate`

Tutorial I

Dave Zes

November 9, 2024

1 Simple Example

Let's simulate a tiny data set:

```
library(mactivate)
set.seed(777)
## tiny
d <- 11
N <- 3000
X <- matrix(rnorm(N*d, 1, 1), N, d)
colnames(X) <- paste0("x", 1:d)
b <- rep_len( c(-1, 1), d )
ystar <-
  X %*% b +
  1/3 * X[, 1] * X[, 2] * X[, 3] -
  1/3 * X[, 3] * X[, 4] * X[, 5] * X[, 6] +
  1/2 * X[, 8] * X[, 9] -
  2 * X[, 1] * X[, 2] * X[, 7] * X[, 11]
xtrue_formula <- eval(parse(text="y ~ . + x1:x2:x3 + x3:x4:x5:x6 + x8:x9 + x1:x2:x7:x11"))
xnoint_formula <- eval(parse(text="y ~ ."))
errs <- rnorm(N, 0, 3)
y <- ystar + errs
Xall <- X
yall <- y
```

```

Nall <- N
dfx <- data.frame("y"=yall, Xall)

```

Let's predict from primary effects only.

```

xlm <- lm(y ~ . , data=dfx)
yhat <- predict(xlm, newdata=dfx)
sqrt( mean( (yall - yhat)^2 ) )

```

```
[1] 6.715759
```

Now let us predict from true model.

```

xlm <- lm(xtrue_formula , data=dfx)
yhat <- predict(xlm, newdata=dfx)
sqrt( mean( (yall - yhat)^2 ) )

```

```
[1] 2.984564
```

Configure hybrid fit control.

```

xcmact_hybrid <-
f_control_mactivate(
param_sensitivity = 10^10,
w0_seed           = 0.1,
w_col_search      = "one",
bool_headStart    = FALSE, ### gradient
max_internal_iter = 500, ##### small -- exits automatically, don't set this too small
ss_stop            = 10^{(-8)}, ### small
escape_rate        = 1.01,
Wadj               = 1/1,
tol                = 10^{(-8)}
)

```

Now fit using hybrid algorithm.

```

m_tot <- 5
Uall <- Xall
xxnow <- Sys.time()
xxls_out <-
f_fit_hybrid_01(
X = Xall,
y = yall,
m_tot = m_tot,
U = Uall,
m_start = 1,
mact_control = xcmact_hybrid,
verbosity = 5
)
cat( difftime(Sys.time(), xxnow, units="mins"), "\n" )

```

Now predict from our hybrid fitted model.

```

class(xxls_out)

[1] "mactivate_fit_hybrid_01"
[2] "list"

yhatall <- predict(object=xxls_out, X0=Xall, U0=Uall, mcols=m_tot)
sqrt( mean( (yall - yhatall)^2 ) )

[1] 2.972347

```